

2112E

Ejector Scraper

Features & Specs

- Top-loading scrapers increase productivity
- AutoLoad™ for smooth loading
- Router bits are adjustable
- Automated water management with iGrade™

| | |
|------------------------|-----------------------|
| Standard Tire Sizes | 23.5 x 25 |
| Overall Length | 31ft. 10in. (9703 mm) |
| Loading Type | Autoload |
| Tandem Hydraulic Lines | Standard |



Specifications

Capacity

| | |
|-----------------|----------|
| Struck capacity | 15 cu yd |
| Heaped capacity | 21 cu yd |

Dimensions

| | |
|--------------------|--------------------|
| Overall dimensions | --- |
| Length | 31 ft10 in.9703 mm |
| Width | 13 ft5 in.4089 mm |
| Height | 7 ft6 in.2286 mm |
| Bucket dimensions | --- |
| Length | 9 ft2 in.2794 mm |
| Width | 12 ft0 in.3658 mm |
| Height | 4 ft1321 mm |

Weight

| | |
|-----------------------------|--------------------|
| Approximate shipping weight | 27,200 lb12,337 kg |
|-----------------------------|--------------------|

Scraper weight distribution

| | |
|--------|-----|
| Tongue | 28% |
| Wheels | 72% |

Tires

| | |
|-----------------------------|-----------|
| Number of tires per scraper | 4 |
| Tire sizes | --- |
| Standard | 23.5 x 25 |
| Option 1 | 26.5 x 25 |
| Option 2 | NA |

Horsepower recommendations

| | |
|---------|---------|
| Minimum | 450 hp |
| Maximum | 575+ hp |

Blades and router

| | |
|------------------------------|----------|
| 2 rows of blade bolts | Standard |
| 6-in. bolt-hole spacing | Standard |
| Straight blade configuration | Standard |
| Drop center configuration | Optional |
| Teeth configuration | Optional |
| Adjustable router bits | Standard |

Hydraulics

| | |
|---------------------------|----------|
| Size of lines and hoses | 3/4 in. |
| Tandem lines | Standard |
| Minimum flow required | 25 gpm |
| Minimum pressure required | 2500 psi |

Precision leveling

| | |
|---------------------|-----|
| GPS/Laser adaptable | Yes |
|---------------------|-----|

Loading type

| | |
|----------------|-----|
| Direct loading | Yes |
| Top loading | Yes |
| Push loading | Yes |
| Autoload | Yes |

Hitches and drawbars

| | |
|----------------------------------|------|
| Hitch type | Yoke |
| Special tractor drawbar required | Yes |

Warranty

| | |
|-------------------------------|----------|
| Six months | Standard |
| Extended warranty (2-3 years) | Optional |

Additional Equipment

| | |
|---------------------------------|----------|
| Yoke-type drawbars | Optional |
| Quick-attach drawbars | Optional |
| Drawbar hitch adapters | Optional |
| Scraper-to-scraper quick-attach | Optional |
| Bolt-on rear bumper | Optional |
| Laser receiver bracket | Optional |
| High-speed leveling skid pads | Yes |

Additional information

Date collected

Product features are based on published information at the time of publication. Product features are subject to change without notice. Contact your local John Deere dealer for more information.

Copyright © 2016 Deere & Company. All Rights Reserved